

**For Residential & Commercial Applications**

Job Name \_\_\_\_\_

Contractor \_\_\_\_\_

Job Location \_\_\_\_\_

Approval \_\_\_\_\_

Engineer \_\_\_\_\_

Contractor's P.O. No. \_\_\_\_\_

Approval \_\_\_\_\_

Representative \_\_\_\_\_

**LEAD FREE\***

**Stainless Steel CinchClamps™ and Close Ear CinchClamps™**

Sizes: 3/8" to 1"

Stainless Steel CinchClamps™ are used to make a leak tight and secure cinched connection of brass (ASTM F1807) or plastic (ASTM F-2159) PEX fittings to PEX (ASTM F-877) CTS sizes SDR9 pipe.

**Specifications**

System shall be plumbed using Watts WaterPEX® cross-linked polyethylene pipe and all joints shall be made using Watts Lead Free\* Brass Crimp Ring™ and/or Poly-alloy CrimpRing™ fittings using the Watts stainless steel CinchClamp™ as outlined in the Watts Installation Guidelines.

**Installation**

Stainless Steel CinchClamps™ must be installed in accordance with all Watts Installation procedures, including information provided in installation manual and guidelines.

Installation of Stainless Steel CinchClamps™ requires the use of a properly calibrated manual, electric or battery operated cinching tool with the proper sized jaw. The tool must be field calibrated to the proper specifications on a regular basis. Refer to proper calibration instructions on the tools instruction sheet.

Watts WaterPEX CinchClamps™ should not be used with wrought copper PEX fittings.

**⚠ WARNING**

If connections must be made in temperatures below 30°F (-1°C), caution must be taken to allow the WaterPEX pipe to form a proper seal against the fitting barb. Apply the connection slowly to ensure the PEX material conforms to the barb.



Stainless Steel CinchClamps



Close Ear CinchClamps

**Approvals**



ASTM NSF

- Manufactured in accordance with American Society for Testing and Materials (ASTM International F877, F1807, F2159, and F2098).
- Listed by the NSF International to NSF Standards 14 and 61 for use in potable water systems.

**Dimensions – Weights**

| MODEL      | SIZE |    | TYPE          | PACKING WEIGHT |      |
|------------|------|----|---------------|----------------|------|
|            | in.  | mm |               | lbs.           | kgs. |
| WP9S-06PB  | 3/8  | 10 | SS CinchClamp | .1             | .05  |
| WP9S-08PB  | 1/2  | 15 | SS CinchClamp | .1             | .05  |
| WP9S-12PB  | 3/4  | 20 | SS CinchClamp | .2             | .09  |
| WP9S-16PB  | 1    | 25 | SS CinchClamp | .2             | .09  |
| WPSCE-08PB | 1/2  | 15 | CE CinchClamp | .1             | .05  |
| WP9CE-12PB | 3/4  | 20 | CE CinchClamp | .1             | .09  |

\*The wetted surface of this product contacted by consumable water contains less than 0.25% of lead by weight.



A Watts Water Technologies Company



USA: Tel: (978) 688-1811 • Fax: (978) 794-1848 • www.watts.com  
 Canada: Tel: (905) 332-4090 • Fax: (905) 332-7068 • www.watts.ca