Engineering Specification

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative
ηριοναι	Tioprosontative
_	

FD-200-K

Floor Drain With Dome Strainer

Specification

Watts FD-200-K epoxy coated cast iron floor drain with anchor flange, weepholes, adjustable nickel bronze dome (standard) strainer, and no hub (MJ) (standard) outlet.

Pipe Sizing			
Suffix	Description		
2	2"(51) Pipe Size		
3	3"(76) Pipe Size		
4	4"(102) Pipe Size		

	. ()			
Outlet Type				
Suffix	Description			
NH	No Hub (MJ)			
P	Push On			

Options				
Suffix	Description			
-5	Sediment Bucket			
-6	Vandal Proof			
-8	Backwater Valve (3, 4" Only)			
-12	Galvanized Top			
-13	All Galvanized			
-15	Strainer Extension (DD-50)			
-113M	Special Epoxy from 3M Range			
-F4-50	4" Round Cast Iron Funnel			
-F4-1	4" Round Nickel Bronze Funnel			
-F6-1	6" Round Nickel Bronze Funnel			
-G-50	4x9" Oval Cast Iron Funnel			
-G-1	4x9" Oval Nickel Bronze Funnel			
-Z	Elastomeric Flange			

Optional Body Material			
Suffix Description			
-60	PVC Body w/Socket Outlet		
-61	ABS Body w/Socket Outlet		

			18			Strainer
_			3/1			Full 4" (102) Throat
	See Chart A See Chart B Weepholes -				2-11/16 (68)	Wide Anchor Flange
	1/2"(13) NPT	- /	Pipe S 2"(51), 3"(76)			B4 Body
	Trap Primer Connection		, ,, - (-,	,, , ,		No HUB (MJ)
						shown

7"(178)

5"(127)

Chart A			
Str. Dia.	Min.	Max.	Free Area Sq. In.
5"(127)	5/8"(16)	1-7/8"(48)	15

Chart B				
Pipe Size	Std. No Hub	P Push On	60/61 PVC/ ABS	
2"(51)	3 5/8"(92)	4"(102)	4"(102)	
3"(76)	3 5/8"(92)	4"(102)	3-3/4" (95)	
4"(102)	3 5/8"(92)	4"(102)	3-3/4"(95)	

NOTICE

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.

WATTS

USA: T: (800) 338-2581 • Watts.com **Canada:** T: (888) 208-8927 • Watts.ca

Latin America: T: (52) 55-4122-0138 ● Watts.com