

Truckin' Reliable Gas Connectors



Blue Hose[®] Food Truck Gas Connector



Rated for performance in temperatures as low as -10° F (-23° C).



Enhanced coating provides UV and antimicrobial protection.



Fulfills IFC 2018 and 2021 food truck gas appliance connection requirements



Discover the Best
Truckin' Gas Connectors

Dormont[®]
A WATTS Brand

Blue Hose®

Food Truck Gas Connector


Your customers count on you to deliver safe, reliable, code-compliant food trucks that stand up to the wear and tear of everyday operation. Now, wherever your customers are, our Blue Hose goes!

- Enhanced antimicrobial coating inhibits growth of bacteria, mold and mildew, and features built in UV protection
- Rated for temperatures as low as -10° F (-23° C)


What's Included In-Box?



Blue Hose®
Food Truck Gas Connector



Full Port Shutoff Valve



F x F Elbows + Pipe Nipples*



90° Street Elbows*

*Contents vary depending on US or Canadian Applications.

ORDERING INFORMATION				
SIZE I.D.	LENGTH			
	24" (610 mm)	36" (914 mm)	48" (1,219 mm)	60" (1,524 mm)
1/2"	1650BPV24BXFT	1650BPV36BXFT	1650BPV48BXFT	1650BPV60BXFT
3/4"	1675BPV24BXFT	1675BPV36BXFT	1675BPV48BXFT	1675BPV60BXFT
1"	16100BPV24BXFT	16100BPV36BXFT	16100BPV48BXFT	16100BPV60BXFT

BTU/HR FLOW CAPACITY NATURAL GAS (FLOW RATING BTU/HR 0.64 SP. GR. @ 0.5 INCH WC PRESSURE DROP)					
MODEL	SIZE I.D.	LENGTH			
		24" (610 mm)	36" (914 mm)	48" (1,219 mm)	60" (1,524 mm)
1650BPFT	1/2"	150,000	120,000	106,000	93,000
1675BPFT	3/4"	291,000	256,000	225,000	198,000
16100BPFT	1"	582,000	512,000	451,000	397,000

CODE ALERT

Fulfills Requirement in IFC 2018 and IFC 2021 calling for a moveable gas appliance connector complying with ANSI Z21.69/CSA 6.16 for Food Truck gas cooking appliance connections



USA: T: (800) 367-6668 • F: (724) 733-4808 • Dormont.com